

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 2/8/2023 Revision date: 2/8/2023 Version: 1.1

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Trade name : MITREPEN

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

Supplier

IPS ADHESIVES 600 ELLIS ROAD DURHAM

NC 27703-6015, USA

1.4. Emergency telephone number

Emergency number : 800-255-3924 (Domestic) +1-813-248-0585 (International)

EHSVelocity 24hrs/7days

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 2 H225 Highly flammable liquid and vapor

Carcinogenicity Category 1A H350 May cause cancer

Specific target organ toxicity (repeated exposure) Category 2 H373 May cause damage to organs through prolonged or repeated

exposure

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)





Signal word (GHS US) : Danger

Hazard statements (GHS US) : H225 - Highly flammable liquid and vapor

H350 - May cause cancer

H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P260 - Do not breathe dust/fume/gas/mist/vapors/spray.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : Safety data sheet available on request.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Ethyl Alcohol	CAS-No.: 64-17-5	< 100	Flam. Liq. 2, H225 Carc. 1A, H350
N,N-DIMETHYL-P-TOLUIDINE	CAS-No.: 99-97-8	≥1-<5	Flam. Liq. 4, H227 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Inhalation), H331 Carc. 2, H351 STOT RE 2, H373
METHANOL usa	CAS-No.: 67-56-1	< 1	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 STOT SE 1, H370

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek medical

advice.

First-aid measures after skin contact : Wash skin with plenty of water. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If

eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : If swallowed, seek medical advice immediately and show this container or label.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after inhalation : Inhalation may cause: irritation (cough, short breathing, difficulty in breathing).

Symptoms/effects after skin contact : Repeated exposure may cause skin dryness or cracking.

Symptoms/effects after eye contact : Irritation to eyes.

Symptoms/effects after ingestion : May be harmful if swallowed.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : dry chemical powder, alcohol-resistant foam, carbon dioxide (CO2).

5.2. Specific hazards arising from the chemical

Fire hazard : Highly flammable liquid and vapor.

Explosion hazard : Vapors may form explosive mixture with air.

Hazardous decomposition products in case of fire : Carbon dioxide. Carbon monoxide. Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

No additional information available

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Avoid contact with skin and eyes. NO open flames, NO sparks, and NO smoking. Ventilate

spillage area.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment.

Emergency procedures : Keep away from combustible material. All equipment used when handling the product must be

grounded. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

No additional information available

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with skin and eyes. Wear personal protective equipment.

Hygiene measures : Do not eat, drink or smoke when using this product. Wear personal protective equipment. Wash

hands and other exposed areas with mild soap and water before eat, drink or smoke and when

leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Storage area : Store away from heat. Store in a well-ventilated place.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2/8/2023 (Revision date) US - en 3/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

MITREPEN		
No additional information available		
Ethyl Alcohol (64-17-5)		
USA - ACGIH - Occupational Exposure Limits		
Local name	Ethanol	
ACGIH OEL STEL [ppm]	1000 ppm	
Remark (ACGIH)	TLV® Basis: URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)	
Regulatory reference	ACGIH 2023	
USA - OSHA - Occupational Exposure Limits		
Local name	Ethyl alcohol (Ethanol)	
OSHA PEL (TWA) [1]	1900 mg/m³	
OSHA PEL (TWA) [2]	1000 ppm	
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1	
N,N-DIMETHYL-P-TOLUIDINE (99-97-8)		
No additional information available		
METHANOL usa (67-56-1)		
USA - ACGIH - Occupational Exposure Limits		
Local name	Methanol	
Local name ACGIH OEL TWA [ppm]	Methanol 200 ppm	
ACGIH OEL TWA [ppm]	200 ppm	
ACGIH OEL TWA [ppm] ACGIH OEL STEL [ppm]	200 ppm 250 ppm	
ACGIH OEL TWA [ppm] ACGIH OEL STEL [ppm] Remark (ACGIH)	200 ppm 250 ppm TLV® Basis: Headache; eye dam; dizziness; nausea. Notations: Skin; BEI	
ACGIH OEL TWA [ppm] ACGIH OEL STEL [ppm] Remark (ACGIH) Regulatory reference	200 ppm 250 ppm TLV® Basis: Headache; eye dam; dizziness; nausea. Notations: Skin; BEI	
ACGIH OEL TWA [ppm] ACGIH OEL STEL [ppm] Remark (ACGIH) Regulatory reference USA - ACGIH - Biological Exposure Indices	200 ppm 250 ppm TLV® Basis: Headache; eye dam; dizziness; nausea. Notations: Skin; BEI ACGIH 2022	
ACGIH OEL TWA [ppm] ACGIH OEL STEL [ppm] Remark (ACGIH) Regulatory reference USA - ACGIH - Biological Exposure Indices Local name	200 ppm 250 ppm TLV® Basis: Headache; eye dam; dizziness; nausea. Notations: Skin; BEI ACGIH 2022 METHANOL	
ACGIH OEL TWA [ppm] ACGIH OEL STEL [ppm] Remark (ACGIH) Regulatory reference USA - ACGIH - Biological Exposure Indices Local name BEI (BLV)	200 ppm 250 ppm TLV® Basis: Headache; eye dam; dizziness; nausea. Notations: Skin; BEI ACGIH 2022 METHANOL 15 mg/l Parameter: Methanol - Medium: urine - Sampling time: End of shift - Notations: B, Ns	
ACGIH OEL TWA [ppm] ACGIH OEL STEL [ppm] Remark (ACGIH) Regulatory reference USA - ACGIH - Biological Exposure Indices Local name BEI (BLV) Regulatory reference	200 ppm 250 ppm TLV® Basis: Headache; eye dam; dizziness; nausea. Notations: Skin; BEI ACGIH 2022 METHANOL 15 mg/l Parameter: Methanol - Medium: urine - Sampling time: End of shift - Notations: B, Ns	
ACGIH OEL TWA [ppm] ACGIH OEL STEL [ppm] Remark (ACGIH) Regulatory reference USA - ACGIH - Biological Exposure Indices Local name BEI (BLV) Regulatory reference USA - OSHA - Occupational Exposure Limits	200 ppm 250 ppm TLV® Basis: Headache; eye dam; dizziness; nausea. Notations: Skin; BEI ACGIH 2022 METHANOL 15 mg/l Parameter: Methanol - Medium: urine - Sampling time: End of shift - Notations: B, Ns ACGIH 2022	
ACGIH OEL TWA [ppm] ACGIH OEL STEL [ppm] Remark (ACGIH) Regulatory reference USA - ACGIH - Biological Exposure Indices Local name BEI (BLV) Regulatory reference USA - OSHA - Occupational Exposure Limits Local name	200 ppm 250 ppm TLV® Basis: Headache; eye dam; dizziness; nausea. Notations: Skin; BEI ACGIH 2022 METHANOL 15 mg/l Parameter: Methanol - Medium: urine - Sampling time: End of shift - Notations: B, Ns ACGIH 2022 Methyl alcohol	

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.

Environmental exposure controls : Avoid release to the environment.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.3. Individual protection measures/Personal protective equipment

Hand protection:				
Туре	Material	Permeation	Thickness (mm)	Penetration
Disposable gloves				

Eye protection:

Туре	Field of application	Characterizations
Safety glasses	Droplet	With side shields

Skin and body protection:

Type

Disposable gloves

Respiratory protection:

Device	Filter type	Condition
Air-Purifying Respirator (APR), reusable	ABEK- Hg/P3	Vapour protection

Personal protective equipment symbol(s):







SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Clear, colorless liquid.

Color : Clear, colourless
Odor : Barely perceptible odour
Odor threshold : No data available
pH : No data available
Melting point : No data available
Freezing point : No data available

Freezing point : No data available
Boiling point : 78 °C based on IMS
Flash point : 13 °C based on IMS
Relative evaporation rate (butyl acetate=1) : No data available
Flammability (solid, gas) : No data available
Vapor pressure : No data available

Relative vapor density at 20°C : 5.77
Relative density : 0.80

Solubility : No data available Partition coefficient n-octanol/water (Log Pow) : No data available

Auto-ignition temperature : 399

Decomposition temperature : No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available Explosion limits : No data available Explosive properties : No data available Oxidizing properties : No data available : No data available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

No additional information available

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Acute toxicity (inhalation)	: Not classified
N,N-DIMETHYL-P-TOLUIDINE (99-97	-8)
LD50 oral rat	1650 mg/kg
LD50 oral	139 mg/kg body weight Animal: mouse, Guideline: other:
LD50 dermal rabbit	> 2000 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal	> 2000 mg/kg
LC50 Inhalation - Rat	1.4 mg/l air Animal: rat, Guideline: other:
LC50 Inhalation - Rat (Vapours)	1.4 mg/l/4h
ATE US (oral)	139 mg/kg body weight
ATE US (gases)	700 ppmV/4h
ATE US (vapors)	1.4 mg/l/4h
ATE US (dust, mist)	0.5 mg/l/4h
METHANOL usa (67-56-1)	
ATE US (oral)	100 mg/kg body weight
ATE US (dermal)	300 mg/kg body weight

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

METHANOL usa (67-56-1)	
ATE US (gases)	700 ppmV/4h
ATE US (vapors)	3 mg/l/4h
ATE US (dust, mist)	0.5 mg/l/4h
Skin corrosion/irritation	: Not classified
N,N-DIMETHYL-P-TOLUIDINE (99-97-	8)
рН	7.44 Temp.: 25 °C Concentration: 1 vol%
Serious eye damage/irritation	: Not classified
N,N-DIMETHYL-P-TOLUIDINE (99-97-	8)
рН	7.44 Temp.: 25 °C Concentration: 1 vol%
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer.
Ethyl Alcohol (64-17-5)	
IARC group	1 - Carcinogenic to Humans
N,N-DIMETHYL-P-TOLUIDINE (99-97-	8)
IARC group	2B - Possibly Carcinogenic to Humans
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
METHANOL usa (67-56-1)	
STOT-single exposure	Causes damage to organs.
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
N,N-DIMETHYL-P-TOLUIDINE (99-97-	8)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
N,N-DIMETHYL-P-TOLUIDINE (99-97-	8)
Viscosity, kinematic	16.364 mm²/s
Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: Inhalation may cause: irritation (cough, short breathing, difficulty in breathing).
Symptoms/effects after skin contact	: Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: Irritation to eyes.
Symptoms/effects after ingestion	: May be harmful if swallowed.

SECTION 12: Ecological information

12.1. Toxicity

·-····································	
Ethyl Alcohol (64-17-5)	
LC50 - Fish [1]	42 – 14200 mg/l
EC50 - Crustacea [1]	2 – 17500 mg/l
N,N-DIMETHYL-P-TOLUIDINE (99-97-8)	
LC50 - Fish [1]	32.036 mg/l

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

N,N-DIMETHYL-P-TOLUIDINE (99-97-8)	
LC50 - Fish [2]	46 – 52 mg/l Pimephales promelas (Fathead minnow)
EC50 72h - Algae [1]	24.37002 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

No additional information available

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

14.1. UN number

DOT NA no. : UN1133 UN-No. (TDG) : Not applicable UN-No. (IMDG) : 1133 UN-No. (IATA) : 1133

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Adhesives
Proper Shipping Name (TDG) : Not applicable
Proper Shipping Name (IMDG) : ADHESIVES
Proper Shipping Name (IATA) : Adhesives

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 3
Hazard labels (DOT) : 3



TDG

Transport hazard class(es) (TDG) : Not applicable

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

IMDG

Transport hazard class(es) (IMDG) : 3
Hazard labels (IMDG) : 3



IATA

Transport hazard class(es) (IATA) : 3
Hazard labels (IATA) : 3



14.4. Packing group

Packing group (DOT) : II

Packing group (TDG) : Not applicable

Packing group (IMDG) : II
Packing group (IATA) : II

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT

UN-No.(DOT) : UN1133

DOT Special Provisions (49 CFR 172.102) : 149 - When transported as a limited quantity or a consumer commodity, the maximum net

capacity specified in 173.150(b)(2) of this subchapter for inner packaging may be increased to 5

L (1.3 gallons).

 $B52 - Not with standing \ the \ provisions \ of \ 173.24b \ of \ this \ subchapter, \ non-reclosing \ pressure \ relief$

devices are authorized on DOT 57 portable tanks.

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110

kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature

during transport, and tf is the temperature in degrees celsius of the liquid during filling.

the flash point of the hazardous material transported is greater than 0 C (32 F).

TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when

DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 173
DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Quantity Limitations Passenger aircraft/rail (49 : 5 L

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 :

CFR 175.75)

DOT Vessel Stowage Location

: 60 L

: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this

section is exceeded.

2/8/2023 (Revision date) US - en 9/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TDG

Emergency Response Guide (ERG) Number : 128

IMDG

Limited quantities (IMDG) : 5 L

Excepted quantities (IMDG) : E2

Packing instructions (IMDG) : P001

Packing provisions (IMDG) : PP1

IBC packing instructions (IMDG) : IBC02

Tank instructions (IMDG) : T4

Tank special provisions (IMDG) : TP1, TR

EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS

EmS-No. (Spillage) : S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS

Stowage category (IMDG) : B

Properties and observations (IMDG) : Adhesives are solutions of gums, resins, etc., usually volatile due to the solvents. Miscibility with

water depends upon their composition.

IATA

PCA Excepted quantities (IATA) : E2 PCA Limited quantities (IATA) : Y341 PCA limited quantity max net quantity (IATA) : 1L : 353 PCA packing instructions (IATA) PCA max net quantity (IATA) : 5L CAO packing instructions (IATA) 364 CAO max net quantity (IATA) 60L Special provision (IATA) A3 ERG code (IATA) 31

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

METHANOL usa CAS-No. 67-56-1 < 1%

METHANOL usa (67-56-1)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ 5000 lb

15.2. International regulations

CANADA

Ethyl Alcohol (64-17-5)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

N,N-DIMETHYL-P-TOLUIDINE (99-97-8)

Listed on the Canadian DSL (Domestic Substances List) inventory.

METHANOL usa (67-56-1)

Listed on the Canadian DSL (Domestic Substances List) inventory.

EU-Regulations

No additional information available

National regulations

Ethyl Alcohol (64-17-5)

Listed on IARC (International Agency for Research on Cancer)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

N,N-DIMETHYL-P-TOLUIDINE (99-97-8)

Listed on IARC (International Agency for Research on Cancer)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

METHANOL usa (67-56-1)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. US State regulations



This product can expose you to N,N-Dimethyl-p-toluidine, which is known to the State of California to cause cancer, and Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision date : 02/08/2023

Full text of H-phrases	
H225	Highly flammable liquid and vapor
H227	Combustible liquid
H301	Toxic if swallowed
H311	Toxic in contact with skin
H331	Toxic if inhaled
H350	May cause cancer
H351	Suspected of causing cancer
H370	Causes damage to organs
H373	May cause damage to organs through prolonged or repeated exposure

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.