



No.	Pièce Part	Composition Material
1	Coulisseau externe Outer Rail	acier
2	Coulisseau interne Inner Rail	
3	Retenue Retainer	
4	Chariot intermédiaire Intermediate member	
5	Billes Ball bearings	
6	Retenu Detent	Polypropylène Polypropylene
7	Levier de dégagement Lift Lever	Nylon 66 Nylon 66
8	Amortisseur Damper SC assembly	Acier inoxydable 304, POM Nylon 66 304 Stainless Steel / POM / Nylon 66
9	Rivets #1 #2 Rivets #1 #2	Acier inoxydable 304 304 Stainless Steel
10	Arrêt Stopper	Nylon 6 Nylon 6
11	Graisse Grease	Grade H1 H1 grade

Numéro de produit Item No.	Longueur de la coulisse mm/ pouces Extension Slide Length mm/inches Travel Length	A	B	C	D	E	F	G	H	Capacité à la paire kg/lbs Load Rating (kg lbs /pair)
COU-SUBSS-SC-16	400 (15-3/4")	128	/	/	/	35.2	/	/	340	37 kg (82 lbs)
COU-SUBSS-SC-18	450 (17-23/32")	128	212.8	/	/	35.2	224	352	390	36 kg (79 lbs)
COU-SUBSS-SC-20	500 (19-11/16")	128	224	/	339	35.2	224	352	440	35 kg (77 lbs)
COU-SUBSS-SC-22	550 (21-21/32")	128	224	/	384	35.2	224	352	490	34 kg (75 lbs)

